

# BRILINE B2



Ideal solution for channel letters with a depth of **80 - 120 mm** and light boxes with **enhanced brightness**.

Due to professional optics directs more light to the surface of illuminated signs.

Cost-effective solution to achieve **more brightness at reasonable price**.

Various color solutions available ● 7500K ● ● ● ● ●

## Specially designed for:

- Channel letters
- Light boxes with enhanced brightness
- Recommended installation depth 80-120 mm

## Features:


- Special optics designed for channel letters
- Compact size
- Efficiency up to **97 lm/W**
- Maximum Tj temperature <80 °C
- **LM80** international certificate for LEDs
- HB fire protection level
- High protection level of IP65
- Light decay < 30% after **50,000 hrs**
- **5 years warranty**




[www.kaisenelectric.com](http://www.kaisenelectric.com)

# KAISEN

## Dimensions



## Light distribution graph



## Technical information

Colors available :	●	●	●	●	○
Power	1 W	1 W	1 W	1 W	1 W
Light output	12 lm	120 lm	15 lm	95 lm	
LED type	2835				
Input	12VDC				
Color temperature	○ 7500 K				
Beam angle	160°				
Protection level	IP 65				
Center-to-Center distance	150 mm				
Working temperature	-30 +50 °C				

## Packing information

Packing type	Chain	Package	Box
Quantity	20 pcs	100 pcs	2500 pcs
Weight	0,16 kg	0,8 kg	19,5 kg

